

DUMOND

DUMOND / SUPER STRENGTH GRAFFITI REMOVER SPECIFICATIONS AND DATA SHEET

1. PRODUCT NAME:

DUMOND / SUPER STRENGTH
GRAFFITI REMOVER

2. MANUFACTURER

National Office:
Dumond Chemicals
1501 Broadway
New York, NY 10036
Phone: (212) 869-6350
FAX: 212-764-5762

3. PRODUCT DESCRIPTION:

DUMOND Super Strength Graffiti Remover is an alkaline/solvent compound designed specifically for removing multiple layers of graffiti and paint from porous masonry surfaces. In almost all instances this product will remove all of the graffiti in a single application and the usual time frame is between 3/5 hours. The product can remain active for up to 24 hours allowing for deep penetration through multiple layers if required. This product is non-flammable and water rinseable. It will remove most spray paints, inks, crayons, markers, etc.

LIMITATIONS:

Product efficiency is reduced during cold weather. Surface and air temperature should be a minimum of 40° during application. This product is not recommended for use on fine wood surfaces nor metal surfaces.

4. TECHNICAL DATA:

FORM: Brown gel
FLASH POINT: None
SPECIFIC GRAVITY: 1.4
WT/BAL. 11.5 LBS.

5. PREPARATORY WORK:

It is often impossible to know the type of graffiti being removed so prior to starting the project test areas should be done that are typical of the surface to be

stripped to ensure that the results will be satisfactory. This will also help the first time user of the product to gauge the correct thickness at which the product should be applied and the time values for removal of the product and graffiti.

6. APPLICATION:

DUMOND Super Strength Graffiti Remover should be applied using synthetic brushes or rollers. Natural fibered brushes are not suitable. Product should be applied at pre-determined thickness (test areas). After the stripping action is finished a putty knife should be used in the removal of the product. The surface should then be power washed to remove the residues of the stripper and graffiti. Masonry surfaces are porous and high pressure water (fan spray) may be necessary to thoroughly flush the deepest graffiti and pigments from the pores of the masonry. Hot water will improve the efficiency of the clean down. The surface should then be neutralized with the DUMOND Neutralizing product.

WE STRONGLY SUGGEST THAT AFTER CLEANING THE SURFACE OF GRAFFITI AN APPLICATION OF THE DUMOND ANTI GRAFFITIANT COATING BE USED. THIS IS A NON SACRIFICIAL CLEAR COATING THAT WILL PROTECT THE SURFACE AND EASE THE REMOVAL OF ANY NEW GRAFFITI.

7. AVAILABILITY AND COST:

All DUMOND products are available through a network of product distributors and paint stores. Call Dumond Chemicals (212-869-6350) for the nearest distributor.

Cost will vary depending on type and conditions to be stripped but in most cases a single application will do the complete removal job. This product has

an average coverage rate of about fifty (50) square ft. to a gallon. Coverage may be greater or less depending upon surface conditions.

8. WARRANTY:

Dumond Chemicals Inc. warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. Dumond Chemicals Inc. liability shall be limited in all events to supplying sufficient products to re-treat the specific areas to which defective product has been applied. Dumond Chemicals Inc. shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of Dumond Chemicals Inc. or its distributors and desires.

9. TECHNICAL SERVICES:

Dumond Chemicals Inc. employs a direct personal assistance staff on hand to answer technical questions to architects, building owners, contractors, etc. Also available are trained sales representatives and technical people for on site assistance. A list of qualified contractors and dealer outlets is also available.

For assistance call our New York office (212-869-6350).

