

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication And WHIMS Standard 29 CFR 1910-1200

Print Date: 05/01/09

Product Name: SEXAUER MULE KICK Product Number: 130898 LIQUID CAUSTIC DRAIN OPENER

PLECE REMIEWE BEEFFOR AND ROWERS AND ENVIRONMENT OF THE PROPERTY OF THE PROPER

Manufacturer: ComStar International Inc.

Tel: 718-445-7900, 800-328-0142

Address:

20-45 128th Street, College Point, NY 11356 Fax: 718-353-5998

Chemical Name: Blended Formula

Synonym(s): None

	MINERORWATTER		
COMPONENTS SODIUM HYDROXIDE	OSHA PEL 2 mg/m3	ACGIH TLV N/A	CAS NO. 1310732
AMMONIUM	50 ppm	N/A	1336-21-6
WATER	N/A	N/A	N/A

III - HAZARDŞIDENTHOATOK FILLE

HMIS Hazard Ratings:

Health - 3, Flammability - 0, Chemical Reactivity - 1

NFPA Hazard Ratings:

Health - 3, Flammability - 0, Chemical Reactivity - 1

NOTE: HMIS and NFPA ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

WEATIRSTEAD MEASURES

Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms persist. Eyes: Immediately flush with plenty of water for at least 15 minutes. Get medical attention. Skin: Remove contaminated clothing, wash affected skin with soap and water immediately. Get

medical attention if symptoms occur. Ingestion: Drink plenty of water. Get immediate medical attention.

V - FRE FIGHTING MEASURES THE HIR IN

Extinguishing Media: All foams, water fog, carbon dioxide (CO2)

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing.

Hazardous Combustion Products: Unknown

Unusual Fire and Exposure Hazards: Reacts negatively with many organic chemicals such as acids and chlorocarbons.

VI - ACCUDENTAL RELEASE MEASURES !!!!!!!

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. For Large Spills: Flush spill area with water spray. Prevent run-off from entering drains, sewers, or streams, collect run-off.

VIII- HANGLING WND STORAGE

Personal Precautionary Measures: Avoid contact with eyes and skin. Wash thoroughly after

handling. Do not breathe vapors or fumes.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials, alkalis and acids.

Store away from heat, sunlight and moisture.

WILL EXPOSURE CONTROLS OF ERSONALIPROTECTION.

Exposure Limits:

ACGIH Threshold Limit Value (TLV): see section !!

OSHA (USA) Permissible Exposure Limit (PEL): see section II

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances such as poorly ventilated spaces, evaporation from large surfaces, spraying, heating, etc.

Respiratory Protection: If engineering controls do not maintain airborne concentrations to an

acceptable level, a NIOSH approved respirator must be worn.

Respirator Type: Organic vapor. If respirators are used, a program should be instituted to assure

Compliance with OSHA Standard 29 CFR 1910.134.

Eye Protection: Wear safety glasses with side shields (or goggles) and a face shield. Skin Protection: It is a good industrial hygiene practice to minimize skin contact.

Recommended Decontamination Facilities: Eye bath, washing facilities

IX PHYSICAL AND CHEMICAL FROMERINES

Color: Clear liquid

Odor: Caustic / ammonia odor Odor Threshold: not available Specific Gravity (H20 = 1): .90 @ 60

Vapor Pressure at 70° F: 420 / 475 mm Hg

Vapor Density (Air = 1): < 1

Evaporation Rate (n-butyl acetate = 1): Same as water

Volatile Fraction by Weight: N/A

Boiling Point: 280° F Melting Point: None

Viscosity at 25° C (77° F): N/A

Solubility in Water: complete

Octanol/ Water Partition Coefficient: not available

Flash Point: None

Lower Explosive Limit 135° C (275° F): N/A Upper Explosive Limit 199° C (390°F): N/A Auto Ignition Temperature (ASTM D 2155): N/A

X - STABILITY AND REACTIMITY : 1

Stability: Product is considered stable.

Incompatibility: Reacts to acids, chlorocarbons, oxidizers, zinc, aluminum and lead

Hazardous Polymerization: not known to polymerize.

XI - FOXICOLOGICAL INFORMATION

Inhalation: Low hazard for usual industrial handling by trained personnel.

Eyes: Causes irritation.

Skin: Low hazard for usual industrial handling by trained personnel, see label warnings.

Ingestion: Non-toxic. Low health hazard.

Acute Toxicity Data:

Oral LD-50 (rabbit): not available inhalation LC-50: not available

XII - ECOLOGICAL INFORMATION IN THE RESERVE TO THE

Introduction: Leaks should be stopped. Spills should be contained and cleaned up immediately. Large liquid spills should be removed by using a vacuum truck. Solid spills should be scooped up and placed in approved containers for disposal. The spill area should then be flushed with water followed by liberal covering of sodium bicarbonate. All clean-up material should be removed and placed in approved containers, labeled and stored in a safe place to await proper treatment or disposal. Spills on areas other than pavement, e.g., dirt or sand, may be handled by removing the affected soils and placing in approved containers. Persons performing clean-up work should wear adequate personal protective equipment and clothing. Spills or releases should be reported, if required, to the appropriate local, state and federal regulatory agencies.

XIII DISPOSAL CONSIDERATIONS

Discharge, treatment, or disposal may be subject to national, state, or local laws. Check with state and local officials before disposal.

XIV TRANSPORTINEORMATION

DOT (USA) Status: not regulated TDG (Canada) Status: not regulated

Air - International Civil Aviation Organization (ICAO) ICAO Status: Check with air freight forwarder for ruling. Sea - International Maritime Dangerous Goods (IMDG)

IMDG Status: not regulated

XV-TREGULATORYINFORMATION IN THE WHEN

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard 29 CFR 910.1200.

OSHA hazardous chemical(s): trade secret (blended formula).

Material(s) known to the State of California to cause cancer: none

Material(s) known to the State of California to cause adverse reproductive effects: none

Massachusetts Substance List: none.

New Jersey Workplace Hazardous Substance List: none

Pennsylvania Hazardous Substance List: none

This document has been prepared in accordance with the MSDS requirements of the WHMIS Controlled Products Regulation.

WHMIS (Canada) Ingredient Disclosure List: trade secret (blended formula).

WHMIS (Canada) Status: not listed.

WHMIS (Canada) controlled material(s): not listed.

WHMIS (Canada) Hazard Classification: not classified.

Carcinogenicity Classification (components present at 0.1% or more): None

International Agency for Research on Cancer (IARC): Not listed

American Conference of Governmental Industrial Hygienist (ACGIH): Not listed National Toxicology Program (NTP): not listed Occupational Safety and Health Administration (OSHA): Not listed

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: None.

SARA (U.S.A.) Sections 311 and 312 hazard classification(s): Not listed.

NOTE: The opinions expressed are those of qualified experts within ComStar International Inc. We believe that the information contained is current as of the date of the Material Safety Data Sheet. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of ComStar International Inc., it is the user's obligation to determine the conditions of safe use of the product.